

FEATURES :

- Heavy Duty and light weight drives. Continuous duty cycle.
- Less sparking of carbon brush under load condition increases the life of carbon brushes and armatures



EDB-0



EDB-1



EDR-2



EDR-3



EDG-2



EDG-3

Supply Voltage Single Phase 50/60 Hz	Drive Model	Drive Speed	No Load R.P.M.	Expansion Range				Drive Weight Kgs.
				Steel Tube O. D.		Copper Tube O. D.		
				inch	mm	inch	mm	
230 V	EDB - 0N	I	2000	1/4" - 3/8"	6 - 10	1/4" - 1/2"	6 - 12	2
	EDB - 1N	I	1000	3/8" - 5/8"	10 - 16	3/8" - 3/4"	13 - 20	2.5
		II	1900	5/16" - 3/8"	8 - 13	5/16" - 1/2"	8 - 13	
	EDR - 2N	I	560	5/8" - 1.1/4"	16 - 28	3/4" - 1.3/8"	19 - 34	7.5
	EDR - 3N	I	380	1" - 1.3/4"	25 - 45	1.1/2" - 2.1/4"	38 - 57	11.3
	EDG - 2N	I	480	5/8" - 1.3/4"	16 - 45	5/8" - 2"	16 - 50	7.5
		II	1080	5/8" - 1.1/4"	16 - 32	5/8" - 1.1/2"	16 - 38	
EDG - 3N	I	130	1" - 3"	25 - 76	1" - 4"	25 - 102	8.5	
	II	430	1" - 2"	25 - 50	1" - 3"	25 - 76		
110 V	EDB - 0N	I	2000	1/4" - 3/8"	6 - 10	1/4" - 1/2"	6 - 12	2
	EDB - 1N	I	1000	3/8" - 5/8"	10 - 16	3/8" - 3/4"	13 - 20	2.5
		II	1900	5/16" - 3/8"	8 - 13	5/16" - 1/2"	8 - 13	
	EDR - 2N	I	560	5/8" - 1.1/4"	16 - 28	3/4" - 1.3/8"	19 - 34	7.5
	EDR - 3N	I	380	1" - 1.3/4"	25 - 45	1.1/2" - 2.1/4"	38 - 57	11.3
	EDG - 2N	I	480	5/8" - 1.3/4"	16 - 45	5/8" - 2"	16 - 50	7.5
		II	1080	5/8" - 1.1/4"	16 - 32	5/8" - 1.1/2"	16 - 38	
EDG - 3N	I	130	1" - 3"	25 - 76	1" - 4"	25 - 102	8.5	
	II	430	1" - 2"	25 - 50	1" - 3"	25 - 76		